SMD Low Profile High Current Molded Inductor
Size 4012

- Molded type
- High satura on current due to CIP material
- Nature air gap and no acous c noise
- Di erent sizes available
- Quan ty: 4000pcs

- High current DC/DC converter
- LC fIter

Dimensions: [mm]







Land Pattern: [mm]



Electrical Properties:

	(µH)			Satura on	(mΩ)	(mΩ)
MD4012-R10N	0.10	±30%	11.5	25	4.30	5.50
MD4012-R22M	0.22	±20%	8.5	20	6.60	8.00
MD4012-R33M	0.33	±20%	7.0	11	13.6	16.0
MD4012-R36M	0.36	±20%	6.5	8.5	15.5	18.0
MD4012-R47M	0.47	±20%	6.0	6.5	18.0	20.0
MD4012-R68M	0.68	±20%	5.0	6.0	32.0	37.0
MD4012-1R0M	1.00	±20%	4.0	6.0	41.0	47.0
MD4012-1R5M	1.50	±20%	3.0	4.0	55.0	63.3
MD4012-2R2M	2.20	±20%	2.8	3.5	69.2	80.0
MD4012-3R3M	3.30	±20%	2.3	3.0	84.0	97.0
MD4012-4R7M	4.70	±20%	2.0	2.5	128	145
MD4012-5R6M	5.60	±20%	1.7	2.3	180	208
MD4012-6R8M	6.80	±20%	1.5	1.7	300	360
MD4012-8R2M	8.20	±20%	1.4	1.6	313	376
MD4012-100M	10.0	±20%	1.3	1.4	410	463
MD4012-220M	22.0	±20%	0.8	1.0	950	1050

Opera ng temperature : -40℃ ~ +125℃
Temperature rise current : The actual value of DC current when the temperature rise is ΔT40℃
Satura on Current will cause L to drop approximately 30%

Typical Electrical Characteristics: