


SMD Shielded Power Inductor
Size 1280




-
-
-
-
-
-
-
-
-
-


Dimensions: [mm]



Land Patterns: [mm]



Schematic:




Electrical Properties:

Part No	Inductance @ 100KHz/0.1V (μ H)	Tolerance	Temperature Rise Current Typ. (A)		DC Resistance Max. (m Ω)	Hi-POT

Typical Electrical Characteristics:

Soldering Reflow:



Preheat condition: 150 ~200°C / 60~180 sec.

Allowed time above 217°C : 60~150 sec.


Max temperature: 260°C .

Max time at max temperature: 5 sec.

Allowed Reflow time: 3x max.


Packaging Information:

Tape Dimension :




Series	A0 (mm)	B0 (mm)	D (mm)	P0 (mm)	P1 (mm)	W (mm)	K0 (mm)	E (mm)	T (mm)
SDDA1280	12.5±0.1	12.5±0.1	1.5±0.1	4.0±0.1	20.0±0.1	24.0±0.3	8.4±0.1	1.75±0.1	0.50±0.05

Peel force of top cover tape:



The peel force of top cover tape shall be between 0.1 to 1.3 N

Reel Dimension: [mm]



Packaging Quantity:

500 Pcs/Reel

2 Reel /Inner box(1000 Pcs)